

DISCHARGING METHOD FOR FLUID SUBSTANCE

Patent number: JP2003231587

Publication date: 2003-08-19

Inventor: KUBO HIROAKI; KISHIDA NENKO; IKEUCHI KUNIHIDE

Applicant: TSUKISHIMA KIKAI CO

Classification:

- international: B29C31/06; B65B37/04; B65D88/66; B65D90/62;
B65G65/40; B29C31/04; B65B37/00; B65D88/00;
B65D90/00; B65G65/00; (IPC1-7): B65D90/62;
B29C31/06; B65B37/04; B65D88/66; B65G65/40

- european:

Application number: JP20020027571 20020205

Priority number(s): JP20020027571 20020205

Report a data error here

Abstract of JP2003231587

PROBLEM TO BE SOLVED: To provide a method for discharging a powder granular substance with which a small amount of the powder granular substance can be discharged even after a discharging port of a hopper is a closed by a valve.

SOLUTION: The method for discharging a fluid substance comprises steps of opening/closing the discharging port 2 by the valve 3 which can vertically rise/lower in the hopper 1 having the discharging port 2 in a lower conic portion and capable of storing the powder granular substance and opening the discharging port 2 to allow the substance to be fed. The valve 3 is lowered step by step from a full open state until a specified value is reached within a range of set values to measure and control a discharged amount. After the valve 3 closes the discharging port 2, the small amount of the powder granular substance is discharged from an annular gap S formed between a hermetic member 13 and the port 2 by an eccentricity of the valve 3 due to vibration until the set value is reached.

COPYRIGHT: (C)2003,JPO

